

# AT-B Series

AUTO LEVEL



## Durable, Dependable, High Value Auto Levels

- 3 Models - 32x, 28x, and 24x Magnifications
- Rapid, Accurate, and Stable Automatic Compensation
- Ultra-Short 20cm (7.9 in.) Focusing
- All-Weather Dependability
- Clamless, Endless Fine Horizontal Adjustments

### AT-B2

High-precision model



Magnification  
**32x**

Objective Aperture  
**42mm**

Accuracy  
**0.7mm**

Minimum Focus  
**20cm**

Protection  
**IPX6**

Weight  
**1.85kg**

### AT-B3A

Versatile model for surveying,  
engineering and construction



Magnification  
**28x**

Objective Aperture  
**36mm**

Accuracy  
**1.5mm**

Minimum Focus  
**20cm**

Protection  
**IPX6**

Weight  
**1.5kg**

### AT-B4A

Economical model for  
engineering and construction



Magnification  
**24x**

Objective Aperture  
**32mm**

Accuracy  
**2.0mm**

Minimum Focus  
**20cm**

Protection  
**IPX6**

Weight  
**1.5kg**

## Rapid, Stable, and Durable Compensator

The compensator of the AT-B series incorporates four suspension wires made of super-high-tensile metal that features minimal thermal expansion coefficient, providing unmatched durability and accuracy. Finely tuned magnetic damping system quickly levels and stabilizes the line of sight despite the fine vibrations present when working near heavy equipment or busy roadways.



## 20cm (7.9 in.) - Ultra-Short Minimum Focus

The AT-B series can focus on objects at 20cm (7.9 in.) in front of the telescope. This feature dramatically facilitates the works in confined spaces.

## Horizontal Circle for Angle Measurement

Horizontal angles can be directly read in 1° or 1gon units. Free rotation feature allows you to read any angle from zero.



## All-Weather Dependability

With the IPX6 rating, the instrument is protected against powerful water jets from all directions, meaning the AT-B series withstands a sudden shower or torrential rainfall.

The advanced protection design also deters clouding or condensation inside the telescope.

SPECIFICATIONS			
	AT-B2	AT-B3A	AT-B4A
<b>Telescope</b>			
Length	215mm (8.46in.)	214mm (8.42in.)	
Magnification	32X	28X	24X
Objective Aperture	42mm (1.65 in.)	36mm (1.42 in.)	32mm (1.26 in.)
Resolving Power	3"	3.5"	4"
Field of View (at 100m/328ft.)	1°20' (2.3m / 7.5ft.)		1°25' (2.5m / 8.2ft.)
Minimum Focus	0.2m (7.9 in.) from end of telescope 0.3m (1ft.) from instrument center		
Image	Erect		
Stadia Constant	0		
Stadia Ratio	100		
Focusing Knob	2-speed	1-speed	
Sighting Aid	Peep Sight		Gun Sight
<b>Accuracy (1km double run leveling)</b>			
Without Micrometer	0.7mm (0.03 in.)	1.5mm (0.06 in.)	2.0mm (0.08 in.)
With Micrometer	0.5mm (0.02 in.)	n/a	
<b>Compensator</b>			
Type	Pendulum compensator with magnetic damping system		
Setting Accuracy	0.3"	0.5"	
Working Range	±15'		
<b>Circular Level</b>			
Sensitivity	10' / 2mm		
<b>Horizontal Circle</b>			
Diameter	103mm (4.1in.)	99mm (3.9in.)	
Minimum Division	1° / 1gon		
<b>General</b>			
Water Resistance	IPX6 (IEC 60529:2001)		
Operating Temperature	-20 to +50°C (-4 to +122°F)		
Size	Width	130mm (5.12in.)	122mm (4.8in.)
	Length	215mm (8.46in.)	214mm (8.4in.)
	Height	140mm (5.5in.)	
Weight	1.85kg (4.1lbs.)		1.5kg (3.3lbs.)

## Standard Package/ Optional Accessories



- AT-B Level
- Hex wrench
- Adjusting pins
- Vinyl cover (AT-B2/B3A)
- Plumb bob(AT-B2/B3A)
- Cleaning cloth
- Lens cap
- User manual
- Hard carrying case



Diagonal Eyepiece DE16 (AT-B2)



Optical Micrometer OM5 (AT-B2)



40x Eyepiece EL5 (AT-B2)

## TOPCON QUALITY Ultimate Environmental Performance and Durability

TOPCON has been performing environmental tests against a set of expected job site conditions to certify the products for long term use. The AT-B Series has been tested by special inspection equipment for complete waterproofness. The AT-B Series also has the highest environmental performance and durability in TOPCON's Auto Level history, proven by tests against temperature, humidity, vibration and drop.



### Water Proof Test (IPX6)

The AT-B Series is proven to withstand powerful water jets from all directions without any submergence inside the unit.



### Cold and Heat Resistance Test

The AT-B Series has passed operating temperature tests from - 20°C to + 50°C degree.



### Durability Test

The AT-B Series has passed strict durability tests including rotation of the leveling foot screw, Focusing knob and Horizontal fine motor screw.



## TOPCON CORPORATION

75-1 Hasunuma-cho, Itabashi-ku, Tokyo 174-8580, Japan  
Phone: (+81)3-3558-2993 Fax: (+81)3-3960-4214  
www.topcon.co.jp

- Specifications may vary by region and are subject to change without notice.
- Windows® is a registered trademark of Microsoft Corporation in the United States and other countries.
- Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Topcon is under license.
- Other trademarks and trade names are those of their respective owners.

## Your local Authorized Dealer is: